



Passivent

North Frith Oasts, Ashes Lane, Hadlow,
Kent TN11 9QU

Telephone **01732 850 770**

Fax **01732 850 949**

Email **projects@passivent.com**

Website **www.passivent.com**

Hybrid Plus2 Aircool Ventilators

Provide hybrid ventilation by means of Passivent Hybrid Plus2 Aircools.

Hybrid Plus2 Aircool, incorporating Aircool ventilator with a mixing chamber. Aircool for masonry walls/windows/ curtain walls* having extruded aluminium frame, extruded aluminium external weather louvres, 4mm black polypropylene insect screen. Insulated motorised controllable dampers fabricated from double skin of aluminium with ABS thermal break and blade compression seals. Mixing chamber finished to RAL 9016 white, incorporating variable speed fan, controllable mixing dampers.

Ventilator U-value 0.86W/m²K when closed. 24V modulating actuator control for dampers and fan controlled by Passivent iC8000 intelligent controller. Fan flow rate of up to 150 l/s. Can be demonstrated to comply with BB93.

Ventilators designed and manufactured under BS EN ISO 9001, and supplied by Passivent, North Frith Oasts, Ashes Lane, Hadlow, Kent TN11 9QU. Tel: 01732 850770, email: projects@passivent.com (and installed by an approved installer).

*Delete as applicable.

